

Solargiga Energy

# Giga Sup7

JMPV-XV6/72-585~600(R)

MONO-CRYSTALLINE BIFACIAL HALF-CUT ANTI-DUST MODULE II

MaximumPower	Maximum Efficiency	PowerTolerance
600W	23.2%	0~+3%



## CELL TYPE

N-Type/MBB/Monocrystalline/Half-Cell



## HIGH EFFICIENCY, HIGH GENERATION

Based on monocrystalline silicon wafer and TOPCon cell technology, the power generation efficiency has greatly improved with lower degradation and better temperature coefficient.



## EXCELLENT ANTI-PID PERFORMANCE

Cell manufacturing technology optimization and materials control will help reduce PID degradation rate to the minimum.



## UNIQUE FRAME DESIGN

Cleaner and effectively reduces power generation losses caused by dust accumulation and improve full life cycle generation gain.



## STRONG MECHANICAL LOAD CAPACITY


Withstand snow pressure up to 5400Pa on the front face and wind pressure up to 2400Pa on the rear face.

12 YEARS

Product Warranty

30 YEARS

Power Output Warranty



First Year Power Degradation : 1% , Subsequent Annual Power Degradation : 0.4%.  
\*please refer to the product warranty for details.

## MANAGEMENT SYSTEM CERTIFICATES

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO 45001: Occupational Health and Safety Management System

ISO 5001: Energy Management System

ISO 14067: Product Carbon Footprint Limited Assurance

ISO 14025: Product Environmental Declaration

IEC 62941: Quality Management System for PV Module Manufacturing

## PRODUCT CERTIFICATES

IEC61215/ IEC61730



\*The specific certificates applicable to different module types and markets will vary, and therefore not all of the certifications listed herein will simultaneously apply to the products you order or use. Please contact your local Solargiga Energy sales representative to confirm the specific certificates available for your Product and applicable in the regions in which the products will be used.

**PICC**  
ADDITIONAL PREMIUM INSURANCE  
SERVICES ARE AVAILABLE



Founded in 2000 , Solargiga Energy Holdings Limited ( 'Solargiga Energy' , HKEX:00757.HK ), is a renewable energy company which combines the business of the whole mono-crystalline industrial chain covering R&D manufacturing , photovoltaic application and global marketing . It 's committed to provide PV products, technical support and integrated system solution for global customers.

Website: [en.solargiga.com](http://en.solargiga.com)  
DS-TS2025V2.1

# MONO-CRYSTALLINE BIFACIAL HALF-CUT ANTI-DUST MODULE GENERATION II

## MODEL NUMBER

JMPV-XV6/72-585~600(R)

## ELECTRICAL PARAMETERS (STC)

Max Power (Pmax/W)	585	590	595	600
Max Power Voltage(Vmp/V)	43.37	43.55	43.72	43.90
Max Power Current (Imp/A)	13.49	13.55	13.61	13.67
Open Circuit Voltage(Voc/V)	52.76	52.98	53.19	53.41
Short Circuit Current (Isc/A)	14.09	14.15	14.21	14.27
Module Efficiency (%)	22.6	22.8	23.0	23.2

STC(Standard Test Condition): AM1.5, Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C

## ELECTRICAL PARAMETERS (NMOT)

Max Power (Pmax/W)	436.53	440.40	444.18	447.96
Max Power Voltage(Vmp/V)	40.42	40.59	40.75	40.91
Max Power Current (Imp/A)	10.80	10.85	10.90	10.95
Open Circuit Voltage(Voc/V)	49.34	49.55	49.74	49.95
Short Circuit Current (Isc/A)	11.37	11.42	11.47	11.52

NMOT(Nominal Module Operating Temperature): Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s

## ELECTRICAL PARAMETERS (BNPI)

Max Power (Pmax/W)	647	654	658	663
Max Power Voltage(Vmp/V)	43.55	43.83	43.90	44.04
Max Power Current (Imp/A)	14.86	14.92	14.99	15.05
Open Circuit Voltage(Voc/V)	52.95	53.23	53.38	53.60
Short Circuit Current (Isc/A)	15.59	15.68	15.72	15.79

BNPI(Bi-facial Nameplate Irradiance): AM1.5, Irradiance: front 1000W/m<sup>2</sup>, rear 135W/m<sup>2</sup>, Cell Temperature 25°C

## TEMPERATURE CHARACTERISTICS

Cell Operating Temperature	45±2°C
Temperature Coefficient of Isc	0.047%/°C
Temperature Coefficient of Voc	-0.240%/°C
Temperature Coefficient of Pmax	-0.280%/°C

## MECHANICAL PARAMETERS

Cell Type	N Type/MBB/Half-Cell	Number of Cells	144 Pcs
Weight		32.5kg	
Front Glass		2.0mm Semi-tempered embossed coated glass	
Back Glass		2.0mm Semi-tempered grid glass	
Frame		Anodized Aluminum	
Dimension		2278 × 1134 × 30mm	
Junction Box		Protection Degree IP68; 3 diodes	
Cable		1×4.0 mm <sup>2</sup> ; +300mm, -200mm /or customized length	

## OPERATING CONDITIONS

Maximum System Voltage	1500V	Max Front Face Static Load (Snow etc)*	5400Pa
Operating Temperature	-40°C~+85°C	Max Rear Face Static Load (Wind etc)*	2400Pa
Maximum Series Fuse Rating	30A		
Bifaciality coefficient	$\varphi_{Voc}=(99\pm 5)\%$ , $\varphi_{Isc}=(80\pm 10)\%$ , $\varphi_{Pmax}=(80\pm 10)\%$		

\*Installation should strictly obey the installation manual of Solargiga Energy

## PACKING INFORMATION

36pcs/pallet	720pcs/40'HQ	864pcs/17.5m flatcar
--------------	--------------	----------------------

\*Power test uncertainty +/-3%







Sales HOT-line: (86)0416 508 1599

E-mail: sales@jz.solargiga.com

Xihai Industry Park, Economic and  
Technical Development Zone,  
Jinzhou , Liaoning Province,China.

Note: Electrical parameters are only used for comparison between different types of modules. Due to product innovation, Solargiga Energy reserves the right to adjust the information in this datasheet at any time without prior notice. The technical data in this datasheet may be slightly deviated. Customer shall obtain the latest version of the datasheet when signing contract and making it an integral part of the binding contract signed by both parties.



DS-TS2025V2.1